



4	高効率電動機搭載 EQUIPPED WITH HIGHLY EFFECTIVE ELECTRIC MOTOR	
3	吸込 溶接金網付 (4メッシュ d0.7) WITH SUCTION WIRE NET (4 MESH d0.7)	
2	電動機	
	保護方式 ENCLOSURE	全閉外扇形 TOTALLY ENCLOSED FAN COOLED TYPE
	出力 OUTPUT [kW]	2.2
	極数・相 POLES · PHASE	2 · 3
	周波数 FREQUENCY [Hz]	50
	電圧 VOLTAGE [V]	200
1	送風機	
	IEコード又は効率基準 IE CODE OR EFFICIENCY STANDARD	IE3
	風量 (MAX.) VOLUME (MAX.) [m³/min]	15
	静圧 (MAX.) [kPa] STATIC PRESSURE	7.60
回転数 SPEED [min ⁻¹]		2900
標準吸込状態 STANDARD SUCTION CONDITION		温度 TEMPERATURE 20℃ 相対湿度 HUMIDITY 65% 絶対圧力 ABSOLUTE P. 101.3 kPa
仕 様 SPECIFICATIONS		

作成 DRAW	S. HATANO	作成日 DATE	2012. 3. 1 MARCH 1, 2012
確認 CONFIRM	S. HATANO	品名 TYPE	U100B-H45-R311
承認 APPROVE	M. TANAKA	図名 TITLE	外形寸法図 EXTERNAL DIMENSIONS
昭和電機株式会社 大東工場 SHOWA DENKI CO., LTD DAITO FACTORY		図番 DRAWING NO.	YU08R31100-0

図 歴 RECORDS	変更日 DATE	変更内容 REVISION	変更 REVISED BY
△×			
△×			
△×			

